



## Mechanical

<b>Dimensions</b>	481.4 x 480 x 132 mm (19 x 18.9 x 5.2")
<b>Weight</b>	16.6 kg (36.6 lb)
<b>Enclosure material</b>	SGCC steel
<b>Mount material</b>	Aluminum
<b>Slide rails support</b>	The rails support 482.6 mm (19") four-post racks with square holes (9.5 x 9.5 mm) and posts depths ranging from 650 to 1000 mm (25.6–39.4")

---

## Hardware

<b>Management interface</b>	Ethernet In-Band
<b>Networking interface</b>	(1) 1/2.5/5/10 GbE RJ45 port (2) 1/10 GbE SFP+ ports
<b>Power method</b>	(2) AC input, 100–240V, 7A Max., 50/60Hz (redundant, hot-swappable)
<b>Power supply</b>	Hot-swappable 550W CRPS
<b>Supported voltage range</b>	100—240V AC
<b>Max. power consumption</b>	410W
<b>Max. power budget for Drives</b>	310W
<b>ESD/EMP protection</b>	Air: ± 12kV, contact: ± 8kV
<b>Button</b>	Factory reset
<b>Ambient operating temperature</b>	-5 to 40° C (23 to 104° F)
<b>Ambient operating humidity</b>	5 to 95% noncondensing
<b>Certifications</b>	FCC, CE, IC

---

## Capacity

<b>HD cameras</b>	210
<b>2K cameras</b>	140
<b>4K cameras</b>	70

---

## LEDs

<b>System</b>	(1) Power: blue/white Flashing white: bootup in progress
---------------	---

Flashing blue: firmware upgrading  
Steady white: factory defaults, awaiting adoption  
Steady blue: device is adopted

**Ethernet**

Green: link/activity

**SFP+**

Green: link/activity

**HDD**

White: disk detected

Amber: disk error

**Stay in Touch**

 

[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.