

Mechanical

Dimensions135 x 72 x 31.8 mm (5.3 x 2.8 x 1.3")Weight168 g (5.9 oz)Enclosure materialsGlass, polycarbonateMount materialAluminum alloy

Mounting

Wall (Included) Gang box mount (Gang box not included)

Hardware

Networking interface	(1) 10/100 Mbps RJ45 port
Management interface	Ethernet
Power method	PoE UL 294 Power-limited Class 2 PSU UL 60950-1/62368-1 LPS/PS2 PSU
Supported voltage range	44-57V DC
Max. power consumption	5W
Display	127 mm (5") diagonal
Resolution	720 x 1280 (9:16)
Display luminance	300 nits (typical)
Touch screen technology	Capacitive multi-touch
Screen orientation	Portrait
Microphone	Yes
Speaker	Yes
Button	Factory reset
Ambient operating temperature	0 to 40° C (32 to 104° F)
Operating environment	Indoor use only
Ambient operating humidity	5 to 95% noncondensing
Software information	The software version of a product can be checked at https://unifi.ui.com
UL 294 level	Destructive attack: Level I Line security: Level I Endurance: Level I Standby power: Level I
UL 294 statement	Compliance with IEEE 802.3 specifications was not verified as part of UL 294. The equipment is intended to comply with the section of the National Electrical Code, ANSI/NFPA 70, Article 725.121, Power Sources for Class 2 and Class 3 Circuits.


PoE cabling requirements	Cable 5e cabling is the minimum performance category recommended. The performance category utilized should match the transmission speed required at the installation site. The minimal conductor gauge permitted to connect between the PSE or power injector and the PD shall be 26 AWG (0.13 mm ²) for patch cords; 24 AWG (0.21 mm ²) for horizontal or riser cable.
CAN/ULC-60839-11-1 Grade	Grade assignment: I
Certifications	CE, FCC, IC, UL 294, CAN/ULC-60839-11-1
Document number, and issue date and/or revision level	UA-Intercom-Viewer, V01

UniFi Intercom Viewer - Tech Specs

Software

Management application

UniFi Access: Version 1.22.17 and later



© 2024 Ubiquiti, Inc. All rights reserved.