

UniFi UISP Branding

Search UniFi products

Switching WiFi Camera Security Door Access CloudKeys & Gateways Power Tech New Ii



Camera Security > G5 PTZ

Datasheet

In The Box

Marketing Images

Installation Guide



Mechanical

Dimensions

Without mount: Ø90 x 152.5 mm (Ø3.5 x 6")
With mount: 90 x 94 x 179.5 mm (3.5 x 3.7 x 7")

Weight

Without mount: 580 g (1.3 lb)
With mount: 650 g (1.4 lb)

Enclosure material

Aluminum alloy, polycarbonate

Mount material

Wall mount: polycarbonate
Pole mount: aluminum alloy

Pole mount diameter

38-50 mm (1.5-2") on pipe outer diameter

Weatherproofing

IP66

Resistance IK04

Optics

Sensor 5MP 1/2.7" CMOS

Lens F 3.42–6.85 mm; f/1.85–f/2.4

View angle 16:9 Wide: H: 99.7°, V: 51.9°, D: 121°
16:9 Tele: H: 45.5°, V: 25.4°, D: 52.4°

Night mode Built-in IR & white LED illumination with IR cut filter

IR distance 20 m (65 ft)

IR limitation Keep distance from top/side ≥60 cm (2 ft)

Video

Resolution 4MP 2688 x 1512 (16:9)

Max. frame rate 30 FPS

System

Networking interface 10/100 MbE RJ45 port

Max. power consumption 14W

Power method PoE+

Supported voltage range 37–57V DC

LEDs R/G/B/W: link, activity
Floodlight: 400 lm

Button Factory reset

Mounting Wall, pole mount (Included)
Conduit adapter, surface, in-ceiling, pendant, corner mount (Optional, sold separately)

Ambient operating temperature -30 to 45° C (-22 to 113° F)

Ambient operating humidity 0 to 90% noncondensing

Certifications FCC, IC, CE

Audio

Microphone Yes (Can be disabled)

Software

Web application UniFi Protect

Mobile app UniFi Protect iOS™ and Android™

Stay in Touch

Email

Subscribe



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.